

Introduction

For double doors where one door is active and the other stationary, select the active set and the matching dummy set. Then go to **section 8A** <u>locks and latches</u> to select the lock. Flush and surface bolts are used on for the inactive door to keep it stationary. Select a traditional surface slide bolt set or an antique style chain head bolt and foot bolt set. Measure the stile (page **14A-14**) of the door to select a width that will fit. Flush bolts may be used on the edge of the inactive door when they need to be hidden. Surface bolts are normally longer on top and shorter on the bottom of the door. Select a length that is easily reached. The active door may have passage, privacy, or entry door functions.

For doors that will be used at the same time, ball or roller catches will hold the doors in place. These are mounted on the top edge of the door and fit into a catch plate on the door frame. The doorknobs on each door will be held in place with <u>dummy spindles</u> (pg. **6B-2**). These are small brackets mounted on the surface of the door. Double doors may require doorknobs on both sides or only on the front side (ex. closets).

Dummy Spindle Threaded & Tapped (16 TPI)

#3101



7mm diameter 1" long 1" base

Sold invididually. Tapped for #1024 standard set screws.

Dummy Spindle Threaded & Non-tapped (20 TPI)

#3117



7mm diameter 15/16" long 1" base

Sold invididually.

Flush Bolt Set



Set includes the pair as shown. Set may be installed on the face or edge of the door.

#3610.US3 #3610.US7 Polished Brass Antiqued Brass

#3610.US9A #3610.US9B Polished Bronze Antiqued Bronze

12" and 8" 1 3/16" width

Narrow Rim Lock Set



Sold as shown. Pair this lock with undersized doorknobs. *Small ceramic knobs pg. **7B-4** *Colonial doorknobs pg. **1F-2**

#2011.US693

Lockbody: Catch: 3 1/2" x 2" 3 1/2" x 3/4"

Charleston Hardware Company

Plain Head Chain Bolts/Foot Bolts



Cast brass and cast iron. Pull chain to release top bolt, lift handle to release foot bolt.

#3627.XXX

* XXX - Available finishes US3A, US7, US19

Head: 5 ^{7/8} x 1 ^{7/8} Foot: 5 ^{7/8} x 1 ^{7/8}

Small Scroll Head Chain Bolts/Foot Bolts



Cast brass and cast iron. Pull chain to release top bolt, lift handle to release foot bolt. For narrow stile doors.

#3606.XXX

* XXX - Available finishes US3A, US7, US19

Head: 3 ^{1/2}″ x 1 ^{7/8}″ Foot: 3 ^{1/2}″ x 1 ^{7/8}″

Large Scroll Head Chain Bolts/Foot Bolts



Cast brass, bronze, and iron. Pull chain to release top bolt, step to engage bottom bolt and kick for release.

#3607.XXX

* XXX - Available finishes US3A, US7, US19, US9A,

Head: 5" x 2 1/8" Foot: 5" x 2 1/8"

US9B

Ball Catch





#3624.XXX

* XXX - Available finishes US10B, US9A, US3, US14, US7, US26, US3A, US19

Charleston Hardware Company